

# BioLaz<sup>®</sup>

## Real-Time Microbial Monitor

Without measurement there is no control.



The BioLaz Real-Time Microbial Monitor provides real-time detection of biological organisms in controlled environments used for the manufacture of sterile products. The sensor can be connected directly to Pharmaceutical Net, FacilityPro<sup>®</sup> SCADA, FacilityPro SMART, or your own software, and is designed for continuous operation.

The BioLaz has been independently tested to meet the rigorous requirements of *USP <1223> Validation of Alternative Microbiological Methods* and of *EP 5.1.6 Alternative Methods for Control of Microbiological Quality*, for the Pharmaceutical market.

BioLaz samples air via a stainless steel sample probe. As the air passes through the system it is illuminated by a laser and the biological particles fluoresce. Those fluorescing biological particles are then counted in one of two size channels, depending on their size.

The BioLaz has been designed with a small footprint in a 316L stainless steel enclosure to fit in constrained space. The unit provides its own air flow using an internal pump, eliminating the cost of and need for external vacuum lines.

### BENEFITS

- Immediate notification when biological particles are present
- Verify biological levels are acceptable prior to filling
- Separation of finished product (based on timing of alarms)
- Immediate notification for alarm response
- Faster batch release
- Reduced operator error
- Paperless data management

### FEATURES

- Capable of single Bio-Count detection: One Bio-Count is representative of 1 CFU
- Validated to USP <1223> and EP 5.1.6 requirements
- Not constrained by physical and biological efficiencies associated with impact air samplers
- Not constrained by the type and quality of the growth media
- Real-time, continuous counting free from error sources including contamination, mishandling, and inaccurate counting
- Easy to operate and does not require any special handling, training, or logistics

### APPLICATIONS

- Sterility test isolators
- Filling lines
- Aseptic transfers
- Biotech applications – product to patient
- Troubleshooting contamination events

### BioLaz 504

<b>Detection methods</b>	Mie scatter for particle detection Fluorescence emission for differentiating biological and inert activity
<b>Minimum resolution</b>	1 Bio-Count (representative of 1 CFU)
<b>Maximum concentration</b>	25,000 Bio-Counts per second
<b>Size range</b>	0.5 µm to 50 µm
<b>Sizing channels</b>	Two-size Channel Mode
<b>Size</b>	9.84 x 7.87 x 5.91 in (25 x 20 x 15 cm) (Box without ISP and handle)
<b>Weight</b>	13.5 lb (6.1 kg)
<b>Operation temperature</b>	32 – 95 °F (0 – 35 °C), 10 – 95% non-condensing relative humidity
<b>Storage temperature</b>	14 – 140 °F (-10 – 60 °C), 10 – 95% non-condensing relative humidity
<b>External chemical resistance</b>	Isopropyl alcohol, acetone, chlorinated solution, hydrogen peroxide
<b>Enclosure material</b>	316L stainless steel
<b>Flow rate</b>	3.6 LPM ± 5%
<b>Power source</b>	85 – 264 VAC, 47 – 63 Hz
<b>Power consumption</b>	15 W
<b>Air outlet filtering</b>	HEPA filter provided (> 99.97% @ 0.3 µm)
<b>Detectors</b>	Photo Multiplier Tube (PMT)
<b>Laser wavelength</b>	405 nm
<b>Data storage</b>	External software: Pharmaceutical Net, FacilitySight, or customer-supplied
<b>Communications</b>	RS-232 and TCP/IP via Ethernet

BioLaz® and FacilitySight® are registered trademarks of Particle Measuring Systems, Inc.  
All other trademarks are the property of their respective owners.  
Particle Measuring Systems, Inc. reserves the right to change specifications without notice.

#### Headquarters

5475 Airport Blvd, Boulder, CO 80301, USA  
Tel: +1 303 443 7100, +1 800 238 1801  
FAX: +1 303 546 7380

#### Instrument Service & Support

+1 800 557 6363

#### Customer Response Center

+1 877 475 3317

[www.pmeasuring.com](http://www.pmeasuring.com)  
[info@pmeasuring.com](mailto:info@pmeasuring.com)



**PARTICLE  
MEASURING  
SYSTEMS**

#### Global Offices

Particle Measuring Systems **UK**  
Tel: +44 1684 581 000  
[pmsemea@pmeasuring.com](mailto:pmsemea@pmeasuring.com)

Particle Measuring Systems **France**  
Tel: +33 160 10 32 96  
[pmsfrance@pmeasuring.com](mailto:pmsfrance@pmeasuring.com)

Particle Measuring Systems **Germany**  
Tel: +49 6151 6671 632  
[pmsgermany@pmeasuring.com](mailto:pmsgermany@pmeasuring.com)

Particle Measuring Systems **Italy**  
Tel: +39 06 9053 0130  
[pmsrl@pmeasuring.com](mailto:pmsrl@pmeasuring.com)

Particle Measuring Systems **Nordic**  
Tel: +45 707 028 55  
[pmsnordic@pmeasuring.com](mailto:pmsnordic@pmeasuring.com)

Particle Measuring Systems **China**  
Tel: +86 21 6113 3600  
[pmschina@pmeasuring.com](mailto:pmschina@pmeasuring.com)

Particle Measuring Systems **Japan**  
Tel: +81 3 5298 8175  
[pmsjapan@pmeasuring.com](mailto:pmsjapan@pmeasuring.com)

Particle Measuring Systems **Singapore**  
Tel: +65 6496 0330  
[pmssingapore@pmeasuring.com](mailto:pmssingapore@pmeasuring.com)

Particle Measuring Systems **Brazil**  
Tel: +55 11 5188 8166  
[pmsbrazil@pmeasuring.com](mailto:pmsbrazil@pmeasuring.com)

Particle Measuring Systems **Mexico**  
Tel: +52 55 2271 5106  
[pmsmexico@pmeasuring.com](mailto:pmsmexico@pmeasuring.com)

Particle Measuring Systems **Puerto Rico**  
Tel: +1 787 718 9096  
[pmspuertorico@pmeasuring.com](mailto:pmspuertorico@pmeasuring.com)